

DN:	5"	SLOTS (mm)		0.25	0.50	0.75	1.00	1.50	2.00
INTERNAL:	129 mm	Fil 90 S	Kg/m	7.6	7.1	6.7	6.4	5.9	5.5
NB TIGES	28	(2.3 x 2,5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
EXTERNAL:	3.7 mm	DE: 140 mm	Bars	13.4	12.2	11.2	10.4	9.0	7.9
		Fil 71	Kg/m	8.7	8.0	7.4	7.0	6.3	5.9
		(1.8 x 3)	% vides	12.2	21.7	29.4	35.7	45.5	52.6
		DE: 141 mm	Bars	22.6	20.1	18.2	16.5	14.0	12.2
		Fil 90	Kg/m	10.1	9.6	9.0	8.5	7.7	7.0
		(2.3 x 3.5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
		DE: 142 mm	Bars	37.0	33.7	31.0	28.6	24.8	21.9
		Fil 106	Kg/m	11.5	10.8	10.2	9.7	8.8	8.1
		(2.7 x 4.2)	% vides	8.5	15.5	21.7	27.0	35.7	42.6
		DE: 143 mm	Bars	61.3	56.2	52.1	48.6	42.8	38.5