

DN:	6"	SLOTS (mm)		0.25	0.50	0.75	1.00	1.50	2.00
INTERNAL:	154 mm	Fil 90 S	Kg/m	8.9	8.3	7.8	7.5	6.8	6.4
NB TIGES	32	(2.3 x 2,5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
EXTERNAL:	3.7 mm	DE: 165 mm	Bars	8.2	7.5	6.9	6.3	5.5	4.9
		Fil 71	Kg/m	10.4	9.3	8.7	8.2	7.3	6.7
		(1.8 x 3)	% vides	12.2	21.7	29.4	35.7	45.5	52.6
		DE: 166 mm	Bars	13.9	12.4	11.2	10.2	8.6	7.5
		Fil 90	Kg/m	11.8	11.2	10.5	9.9	9.0	8.1
		(2.3 x 3.5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
		DE: 167 mm	Bars	22.8	20.8	19.1	17.6	15.3	13.5
		Fil 106	Kg/m	13.5	12.7	11.9	11.3	10.3	9.5
		(2.7 x 4.2)	% vides	8.5	15.6	21.7	27.0	35.7	42.6
		DE: 168 mm	Bars	38.0	34.8	32.3	30.1	26.5	23.8
		Fil 118	Kg/m	15.6	14.6	13.9	13.2	12.0	11.1
		(3 x 5)	% vides	7.7	14.3	20.0	25.0	33.3	40.0
		DE: 170 mm	Bars	60.2	56.0	52.2	49.0	43.5	39.1