

DN:	7"	SLOTS (mm)		0.25	0.50	0.75	1.00	1.50	2.00
INTERNAL:	179 mm	Fil 90 S	Kg/m	10.5	9.8	9.3	8.9	8.2	7.6
NB TIGES	40	(2.3 x 2,5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
EXTERNAL:	3.7 mm	DE: 190 mm	Bars	5.4	4.9	4.5	4.2	3.6	3.2
		Fil 71	Kg/m	11.9	11.0	10.3	9.7	8.7	8.0
		(1.8 x 3)	% vides	12.2	21.7	29.4	35.7	45.5	52.6
		DE: 191 mm	Bars	9.1	8.1	7.3	6.7	5.7	4.9
		Fil 90	Kg/m	13.8	13.1	12.3	11.7	10.6	9.6
		(2.3 x 3.5)	% vides	9.8	17.9	24.6	30.3	39.5	46.5
		DE: 192 mm	Bars	15.0	13.7	12.6	11.6	10.1	8.9
		Fil 106	Kg/m	15.8	14.8	14.0	13.3	12.1	11.2
		(2.7 x 4.2)	% vides	8.5	15.6	21.7	27.0	35.7	42.6
		DE: 193 mm	Bars	25.1	23.0	21.4	19.9	17.5	15.8
		Fil 118	Kg/m	18.1	17.1	16.2	15.4	14.1	13.0
		(3 x 5)	% vides	7.7	14.3	20.0	25.0	33.3	40.0
		DE: 195 mm	Bars	40.0	37.2	34.7	32.5	28.9	26.0
		Fil 134	Kg/m	20.9	19.8	18.8	17.9	16.4	15.2
		(3.4 x 6)	% vides	6.8	12.8	18.1	22.7	30.5	37.0
		DE: 197 mm	Bars	64.8	60.8	57.1	53.9	48.4	43.8

