



BRIDGE SLOT SCREENS

Slot Openings mm	Tubafor high density			Standard Tubafor						According to DIN 4922					
	Short Punch			Medium Punch			Short Punch			Medium Punch			Long Punch		
	Thickness			Thickness			Thickness			Thickness			Thickness		
	3	3,5	4	3	4	5	3	3,5	4	4	5	6	5	6	8
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
0,50	4,83	4,83	4,83	3,83	3,83	3,83	-	-	-	-	-	-	-	-	-
0,75	7,37	7,37	7,37	5,83	5,83	5,83	-	-	-	-	-	-	-	-	-
1,00	10,00	10,00	10,00	7,90	7,90	7,90	9,04	9,04	8,39	6,58	6,17	5,81	5,72	5,45	4,97
1,25	12,67	12,67	12,67	10,03	10,03	10,03	11,57	11,57	10,73	8,08	7,59	7,16	7,30	6,95	6,34
1,50	15,43	15,43	15,43	12,22	12,22	12,22	14,11	14,11	13,08	9,59	9,02	8,52	8,89	8,46	7,72
2,00	21,20	21,20	21,20	16,78	16,78	16,78	18,14	18,14	16,94	13,21	12,43	11,74	11,64	11,11	10,18
2,50	27,27	27,27	27,27	21,59	21,59	-	23,58	23,58	22,03	16,05	15,17	14,38	14,32	13,70	12,60
3,00	32,70	32,70	32,70	25,89	25,89	-	27,33	27,33	25,59	19,86	18,77	17,79	17,72	16,96	15,60
3,50	-	-	-	-	-	-	-	-	-	22,50	21,33	20,25	20,38	19,53	18,03
4,00	-	-	-	-	-	-	-	-	-	26,56	25,18	23,90	23,96	22,96	21,19