



## DEEP WELL PLAIN CASINGS

Indication of depth range in meters- 1st meterage = solid casing (SDR) followed by max depth of screen	Outside & Inside diameter in mm	Wall thickness in mm	Weight kg/m	Max. Joint stripping load kN	Collapse resistance in Bar kp/cm <sup>2</sup>	SDR Ratio/Psi
100 - 150	63 x 53	4.7	1.31	11.00	16.24	13.5/471
100 - 150	75 x 63	5.6	1.37	12.35	16.12	13.5/471
100 - 150	90 x 76	6.7	2.67	10.23	16.53	13.5/471
100 - 150	110 x 94	8.2	4.01	30.53	16.45	13.5/471
100 - 150	125 x 110	7.1	4.02	55.00	15.44	17/224
100 - 150	140 x 123	8.5	5.35	50.00	15.45	17/224
100 - 150	160 x 135	9.7	6.92	60.00	15.21	17/224
100 - 150	165 x 145	9.5	7.07	65.00	15.44	17/224
100 - 150	186 x 167	9.5	8.10	60.00	15.17	19/220
100 - 150	200 x 176	12.1	10.82	80.00	15.31	16/222
100 - 150	225 x 197	13.6	13.75	90.00	15.31	16/222
80 - 120	315 x 275	19.4	26.30	120.00	15.31	16/222