



MEDIUM WELL PLAIN CASINGS

| Indication of depth range in meters - 1st meterage = solid casing (SDR) followed by max depth of screen | Outside & Inside diameter in mm | Wall thickness in mm | Weight kg/m | Max. Joint stripping load kN | Collapse resistance in Bar kp/cm ² | SDR Ratio/Psi |
|---|---------------------------------|----------------------|-------------|------------------------------|---|---------------|
| 100m - 120m | 110 x 99 | 5.1 | 2.53 | 35 | 7.93 | 21/115 |
| 100m - 120m | 113 x 102 | 5.5 | 2.86 | 40 | 8.12 | 21/115 |
| 100m - 120m | 125 x 114 | 6.3 | 3.58 | 45 | 8.5 | 19/200 |
| 100m - 120m | 140 x 127 | 6.5 | 4.10 | 50 | 8.6 | 21/115 |
| 100m - 120m | 160 x 146 | 7.4 | 5.35 | 58 | 8.5 | 21/115 |
| 100m - 120m | 165 x 150 | 7.5 | 5.76 | 65 | 8.5 | 21/115 |
| 100m - 120m | 186 x 169 | 8.5 | 7.30 | 70 | 8.6 | 17/224 |
| 100m - 120m | 200 x 181 | 9.1 | 8.36 | 80 | 8.6 | 17/224 |
| 100m - 120m | 225 x 203 | 10.8 | 11.10 | 100 | 8.5 | 19/220 |
| 100m - 120m | 250 x 227 | 11.5 | 13.12 | 110 | 8 | 16/222 |
| 50m - 80m | 315 x 283 | 14.5 | 20.84 | 100 | 7.5 | 16/222 |